



### **Sliding solutions**

From family homes to high performance workplaces, Brio sliding systems are the secret to transforming and making the most of any space.

Designed to be quiet, safe and easy to use, Brio hangers feature precision bearings and durable conical wheels. They are also designed to remove fiddly, loose components and provide set and forget locking technology.

Versatility is a core element of our design. These sliding systems can be used in both residential and commercial environments and suit a range of door and shutter constructions such as timber, aluminium, and composite materials.

Our Quick Run system is designed for interior sliding doors up to 120kg in weight, while the Pro Run systems are designed for doors up to 200kg and 400kg in weight. Both ranges can be face fixed to a reveal or mounted into a recess for a streamline solution. Track configurations allow for single panels sliding, dual panels bi-parting or multiple parallel tracks for bypassing and stacking openings.

Brio's variety of hanger and guide choices means our systems can be used in a range of applications:

- · Internal pocket doors
- External shutters
- · Room dividers
- Patio and balcony doors
- · Large glazed facades

Systems are also designed to operate with Brio's soft close accessories which can be used with doors as heavy as 300kg. The neat design allows our soft closers to be housed inside the track, ensuring minimum clearances between track and panel are maintained while doors close quietly and safely.



### **Quick Run 120**

Suitable for aluminium and timber panels up to 120kg, this system provides quick and easy installation with secure locking for peace of mind.

The four engineered polymer, conical shaped wheels provide whisper quiet operation while the high-precision steel bearings allow fingertip control. The unique design ensures a straight running panel and lower operating force.

Purchased as components or in convenient kits, Quick Run systems use the adjustable clip stop 120CS to secure panels as standard but can easily integrate with the 120SCT soft close for superior operation. Additional accessories include a track fascia to dress face fixed systems and our telescopic kits which allow multiple panels to traverse an opening in synchronisation, perfect for wide openings and room dividers.

Brio Quick Run 120 hangers offer three versatile designs which when combined with our multiple track and guide options, provide a solution for every application. All Quick Run 120 tracks are available in 25µm clear anodising for improved corrosion performance.

#### **Specifications**

Max panel weight:	120kg
Min panel thickness:	28mm

### **Optional Accessories**

Soft Close:	120SCT (40-120kg panel)
Telescopic:	TEL/2 (Max panel weight 120kg)
	TEL/3 (Max panel weight 100kg)
Simultaneous:	SIM/2 (Max panel weight 120kg)
Track Fascia:	123
Door Collector:	924-DC

### **Common Application Solutions**

#### Aluminium glazing



120C track designed to integrate with ceiling tiles



installation



105AA guide with built in adjustment for aluminium panels

## Surface mount multiple stacking



120E track can be soffit or face fixed, operates with telescopic & simultaneous kits



mount installation 106A/94 guide designed for

multiple

panels



## Zero clearance pocket door



120F track can be flush mounted for a clean look



61JNP hanger provides minimal clearance between track and panel



94PPA channel suitable for 104W/94 (shown), 106A/94 and 106E/94 guides







### **Pro Run**

The Pro Run systems are the most versatile and robust of all the Brio straight sliding options. Able to accommodate aluminium and timber panels from 120 to 400kg, it is suited to both internal and external applications.

Pro Run features all the versatility and engineering of the Quick Run system, but with the ability to support heavier panels and larger glazed openings. This allows uninterrupted views while protecting spaces from the elements.

Hanger bodies are made from cast stainless steel and feature six precision stainless steel bearings which have larger wheel diameter, providing an even smoother operation.

To prevent large panels becoming a safety hazard, Pro Run systems come with a dampener stop as standard and have an optional, market leading, soft close for panels up to 300kg.

This system is compatible with the Brio telescopic kits and our simultaneous kit which connects two bi-parting panels to open and close in unison, creating a truly grand entrance.

### **Specifications**

Max panel weight:	400kg
Min panel thickness:	40mm

### **Optional Accessories**

Door Collector:	924-DC
Track Fascia:	403E
Simultaneous:	SIM/2 (Max panel weight 120kg)
Telescopic:	TEL/2 (Max panel weight 120kg) TEL/3 (Max panel weight 100kg)
Soft Close:	200-SC (Panel weight 120-200kg) 300-SC (Panel weight 201-300kg)

57SS/M: Surface mount



58SS/M: Recessed mount



61SS/M: Zero clearance:



400-DS: Damper Stop

300-SC: Soft Close



# **Specifications**

SYSTEMS	QUICK RUN 120	PRO RUN 200	PRO RUN 40
TRACKS & FASCIAS			
ntegrate with ceiling tiles	120C	-	-
Groove for weatherstrip, fascia or TEL/SIM accessories	120E	-	400E
Flush mounting	120F	200F	400F
Anodised aluminium fascia with end caps - 2m	123-20CA*	-	403E-20CA*
Anodised aluminium fascia with end caps - 3m	123-30CA*	-	403E-30CA*
Anodised aluminium fascia with end caps - 4m	123-40CA*	-	403E-40CA*
Anodised aluminium fascia with end caps - 6m	123-60CA*	-	403E-60CA*
Track end caps pair	-	400F-EC	400F-EC
BRACKETS			
Single face fix	1SS/250	1SS/250	1SS/250
Double face fix	5SS/120	5SS/250	5SS/250
HANGERS	,		
Timber & metal panels - recessed plate	58JNP	58SS/M	58SS/M
Timber & metal panels - surface mount	57JNP	57SS/M	57SS/M
Timber & metal panels - surface mount	-	57SS/MN	57SS/MN
Timber & metal panels - zero clearance	61JNP	61SS/M	61SS/M
Timber & Metal pariets - zero clearance	-	52SS/M	52SS/M
Metal Panel - long bolt		56SS/ML	56SS/ML
		3033/WL	3033/WL
GUIDES	10111		
Timber panels - nylon guide	101N		
Timber multiple panels - adjustable guide, T-slot	106AT	106AT	106AT
Aluminium panels - adjustable guide	105AA	105AA	105AA
GUIDES WITH CHANNEL	,	,	
Pocket door guide with bearing	104W/94PR	104W/94PR	104W/94PR
Recess or surface mount plate with bearing	106E/94	106RB/94	106RB/94
Multiple panels - adjustable guide with bearing	106A/94	106A/94	106A/94
Fimber panels - angle frame (use with 52SS/M)		21RB/94	21RB/94
CHANNELS			
Poly & aluminium anodised - 2m	94PPA-A20	94PPA-A20	94PPA-A20
Poly & aluminium anodised - 3m	94PPA-A30	94PPA-A30	94PPA-A30
Poly & aluminium anodised - 4m	94PPA-A40	94PPA-A40	94PPA-A40
Poly & aluminium anodised - 6m	94PPA-A60	94PPA-A60	94PPA-A60
ACCESSORIES			
Clip Stop	120CS	-	_
Dampener Stop	-	200-DS	400-DS
Soft Close	120SCT	200-SC	300-SC
Telescopic accessory kit - 2 panels	TEL/2	TEL/2	TEL/2
Telescopic accessory kit - 3 panels	TEL/3	TEL/3	TEL/3
Simultaneous accessory kit - 2 panels	SIM/2	SIM/2	SIM/2
Door collector	924-DC	-	-
	02 <del>-1</del> DO		

All rights reserved. Material and design specification subject to change without notice. Product colour reproduction is as near to actual product colour as production methods allow. Warning: Products in this brochure are the subject of registered designs and patents. This brochure relates to Australian products only and some product, design or specifications may differ in other countries.

#### **Allegion Australia**

Freephone 1800 098 094
Freefax 1800 098 095
Email info.au@allegion.com
www.allegion.com.au

**Allegion New Zealand** 

Freephone 0800 447 869
Freefax 0800 447 868
Email nzinfo@allegion.com

www.allegion.co.nz

