

## Application

Widely used in the residential and shutter applications.

To cover any width of opening, any number of doors can be used.

To accommodate different building designs, doors can slide to one or both sides.

Where doors are fitted externally, a canopy is recommended.

## Door Specification

### Track System:

For Individual Doors:

Max Door Height

Max Door Weight Nylon Tyre Hanger

Door Thickness

### Single Run 80

3000mm

80kg

28-48mm

For ease of operation it is recommended that the door width should not exceed 75% of door height.

Timber doors for interior use can be of flush construction or glazed.

Timber doors for industrial applications should be framed, ledged and braced.

Metal doors should be constructed of box section, channel or angle framing, well braced and clad with flat or corrugated sheets.

## Standard Sets and Packs

Sets comprise of top track, hangers, doors stops, nylon guides, screws and instructions.

Set No.	Max. Door Width	Track Length
SR80-20/1	950mm	2000mm
SR80-30/1	1450mm	3000mm
<b>Pack No.</b> SR80-1PK	Fitting pack only no track.	

## Hardware Specification

### Track:

Material

Finish

Standard Lengths

80A

Aluminium

Mill or clear anodised

2000mm, 3000mm, 4000mm and 6000mm

### Brackets:

Face fitted stainless steel, angle

Double face fitted bracket SS

Fit at 600mm maximum centres

91

5SS/120

### Hangers (2 per door):

#### Hangers:

Timber doors - plate (surface)

57ENP

Full Stainless

57SS/ENP

All hangers suffixed 'N' have nylon tyre wheels and are fitted with ball race bearings.

Nylon tyre wheel hangers should not be used on installations involving temperatures exceeding 80°C.

#### Guides:

Timber doors - SS plate fitting

106E/94

Timber doors - nylon guide

101N

Multiple doors

102W/94SS

#### Channels:

Aluminium

94A Aluminium

94PPA Aluminium support & Polypropylene

Aluminium - Mill or Clear Anodised

2000mm, 3000mm, 4000mm and 6000mm

Finish

Standard lengths

Brass

94B

Standard Lengths

2000mm, 3000mm, 4000mm and 6000mm

#### Accessories:

Flush pulls

401

Door stop

120DS

Locks

6400 Series Sliding mortice locks

Flush Bolts

456

Flush bolts and flush pulls are available in (PVD) PVD Brass, (SN) Satin Nickel & (PN) Polished Nickel



