

Application

Designed to achieve minimal clearances of just 3mm between the top edge of the door and underside of the track concealing all moving parts.

Ideally suited to floor to ceiling straight sliding timber doors in both residential and commercial applications.

The smooth track profile can be easily recessed into ceiling to further enhance the clean-lines of the applications.

Door Specification

Track System:

For Individual Doors:

Max Leaf Height

Max Leaf Weight

Min Door Thickness

For ease of operation it is recommended that the door width should not exceed 75% of the height of the door. Timber doors for interior use can be flush construction or glazed.

Zero Clearance 80

3000mm

80kg

35mm

Hardware Specification

Track:

Material

Standard Lengths

80A

Aluminium Clear Anodised

2000mm, 3000mm, 4000mm and 6000mm

Hangers:

Timber doors

61ENP

Stainless steel hangers are fitted with nylon tyre wheels on precision stainless steel ball bearings. Vertical adjustment is simple and positive.

Guides:

Timber Doors

Sawcut Guide

Stainless precision bearing

Nylon spring load guide

Multiple Doors

Spring Guide

101N

106E/94

108N/814

102W/94SS

801S

Channels:

Aluminium

94A Aluminium

94P Polypropylene - Black

94PPA Aluminium support & Polypropylene

81 Aluminium

814 Aluminium Rail

Finish

Standard lengths

Aluminium - Mill or Clear Anodised

2000mm, 3000mm, 4000mm and 6000mm

Accessories:

Flush Pulls

Door Stop

Locking

401

20DS

6400 Series Sliding mortice locks

456 Flush Bolts

PVD Brass, Satin Nickel & Polished Nickel

Finishes:



